

ZD7160

固定扫描器

Fixed Mount On Screen 2D Barcode Reader

嵌入式读码器

Embedded Code Reader



大视野

Large field of view

- 物体自感应
- 内置 RS232 和 USB 接口
- 超大扫描窗口+超薄时尚设计

- 多国语言条码信息直传
- 大视角影像感光器
- 支持无背景光屏幕条码读取

ZD7160

技术规格书 Technical Specification

物理参数 Physical Characteristics

重量 Weight	75g
尺寸 Dimensions	81.5mm L * 71.2mm H * 51mm D
电压 Voltage	5 VDC
电流 Current	220mA
接口支持 Interfaces Supported	USB, RS232

性能参数 Performance Characteristics

光源 Light Source	617nm LED (瞄准 aimer)、6500K LEDs (照明 illumination)
传感器像素 Image (Pixels)	752*480 CMOS
视场角 Field of View	115° (H) ×90° (V)
旋转倾斜偏转 Roll / Pitch / Yaw:	360°, ±65°, ±60°
打印对比度 Print Contrast:	20% minimum reflective difference
支持条码类型 Symbology Decode Capability	1D: UPC, EAN, Code 128, Code 39, Code 93, Code 11, Matrix 2 of 5, Codabar Interleaved 2 of 5, MSI Plessey, GSI DataBar, China Postal, Korean Postal, etc 2D: PDF417, MicroPDF417, Data Matrix, Maxicode, QR Code, MicroQR, Aztec, Hanxin, ect.
条码精度 Minimum Resolution	5 mil Code39

环境参数

工作温度 Operating Temperature:	-25°C to 70°C
存储温度 Storage Temperature	-40°C to 70°C
相对湿度 Humidity:	0% to 95% (非凝结状态)
抗震动 Shock Specifications:	Designed to withstand 1.5m(5') drops

Decode Ranges

5mil	0mm-10mm
13mil	0mm-30mm

Performance may be impacted by bar code quality and environmental conditions